



GENERAL NOTES

- ALL MODIFICATIONS TO THIS PLAN MUST BE PREAPPROVED IN WRITING BY THE DESIGN ENGINEER AND THE LOCAL BOARD OF HEALTH. ALL MODIFICATIONS MADE WITHOUT APPROVAL FROM THE DESIGN ENGINEER OR THE LOCAL BOARD OF HEALTH ARE THE SOLE RESPONSIBILITY
- . ALL CONSTRUCTION METHODS AND MATERIALS SHALL CONFORM WITH THE REQUIREMENTS OF THE LOCAL BOARD OF HEALTH AND THE STATE ENVIRONMENTAL CODE TITLE 5.
- THE CONSTRUCTION OF PERMANENT STRUCTURES UPON THE DISPOSAL SYSTEM OR RESERVE
- . TO OBTAIN A CERTIFICATE OF COMPLIANCE, THREE INSPECTIONS WILL BE REQUIRED BY THE 1) BOTTOM INSPECTION FOLLOWING THE EXCAVATION OF TOPSOIL & SUBSOIL
- MACHINERY THAT MAY CRUSH OR DISTURB THE PIPE SHALL NOT BE ALLOWED ON THE DISPOSAL
- . THIS SYSTEM WAS NOT DESIGNED TO FACILITATE A GARBAGE DISPOSAL
- TOPSOIL, SUBSOIL, PEAT, FILL, AND OTHER IMPERVIOUS MATERIALS SHALL BE REMOVED FROM ALL AREAS WITHIN THE LEACHING FACILITY AND FOR A DISTANCE OF 5 FEET IN ALL DIRECTIONS
- 8. WHERE A SEWAGE DISPOSAL SYSTEM IS TO BE CONSTRUCTED IN FILL, THE FILL SHALL BE PLACE AND COMPACTED IN NO GREATER THAN 12 INCH LIFTS OR ALLOWED TO SETTLE FOR A MINIMUM OF ONE YEAR. THE FILL MATERIAL MUST CONFORM WITH THE REQUIREMENTS OF THE LOCAL BOARD OF HEALTH AND STATE ENVIRONMENTAL CODE TITLE 5, SECTION 15.255
- ENGINEER PRIOR TO CONSTRUCTION.
- . THE BASE FOR THE SEPTIC TANK, PUMP CHAMBER, AND DIST. BOX MUST BE COMPACTED BY A
- INTERIOR PLUMBING SHALL BE CONNECTED TO THE PROPOSED SEPTIC SYSTEM WITH THE
- WELLS WITHIN 100' OF THE PROPOSED SEPTIC SYSTEM ARE SHOWN.
- APPLICABLE STATE AND LOCAL PERMITS SHALL BE ACQUIRED PRIOR TO COMMENCEMENT OF
- . HYDRAULIC CEMENT IS REQUIRED TO SEAL ALL CONNECTIONS AT THE SEPTIC TANK, PUMP
- ORDER TO LOCATE THEM ONCE BURIED. IT IS RECOMMENDED THAT NEW ENGLAND ENVIRONMENTAL DESIGN, LLC. IS RETAINED TO
- STAKE OUT THE PROPOSED SUBSURFACE SEWAGE DISPOSAL SYSTEM IN THE PROPOSED
- FUNCTION AS INTENDED OR THAT IT WILL FUNCTION FOR A DISCLOSED
- FEST HOLE INFORMATION SHOWN REPRESENTS SOILS AT THAT LOCATION ONLY, AND IS NOT TO BE CONSIDERED AN IMPLIED OR EXPRESSED WARRANTY OF THE SOILS BEYOND THE LIMITS OF THE TEST HOLES.

- ALL MATERIALS FOR S.D.S. CONSTRUCTION ARE TO BE INSTALLED IN 6" LIFTS
- CLEAN TITLE 5 SAND IS REQUIRED.
- TITLE 5 SAND CERTIFICATE MUST BE SUBMITTED TO THE BOARD OF HEALTH AND THE DESIGN ENGINEER PRIOR TO CONSTRUCTION.
- USE CAUTION WHILE BACKFILLING.

SOIL EVALUATION

SOIL EVALUATOR: JULIAN P. VOTRUBA SE# 2519 - WITNESSED BY: CEDRIC RICHARDSON - DATE PERFORMED: 4/2/2024

DEEP HOLE	-1			ELE	EVATION=632.0	DEEP HOLE	ELEVATION=				
DEPTH FROM SURFACE (INCHES)	SOIL HORIZON	SOIL TEXTURE (USDA)	SOIL COLOR (MUNSELL)	SOIL MOTTLING	OTHER (STRUCTURES, STONES, BOULDERS, CONSISTENCY, & % GRAVEL)	DEPTH FROM SURFACE (INCHES)	SOIL HORIZON	SOIL TEXTURE (USDA)	SOIL COLOR (MUNSELL)	SOIL MOTTLING	OTHER (STRUCTURES, STONES, BOULDE CONSISTENCY, & % GRAVEL)
0-4"	A	LS	10YR 3/4		LOOSE						
4-12"	В	LS	10YR 5/6		LOOSE						
12-96"	С	SAND /GRAVEL	2.5Y 3/4	10YR 5/8 @ 84"	LOOSE						

l	DEEP HOLE	DEEP HOLE-1A ELEVATION=632.0							DEEP HOLE-2A				
	DEPTH FROM SURFACE (INCHES)	SOIL HORIZON			SOIL MOTTLING	OTHER (STRUCTURES, STONES, BOULDERS, CONSISTENCY, & % GRAVEL)	DEPTH FROM SURFACE (INCHES)	SOIL HORIZON	SOIL TEXTURE (USDA)	SOIL COLOR (MUNSELL)	SOIL MOTTLING	OTHER (STRUCTURES, STONES, BOULDERS, CONSISTENCY, & % GRAVEL)	
	0-4"	A	LS	10YR 3/4		LOOSE							
	4-12"	В	LS	10YR 5/6		LOOSE							
	12-96"	C	SAND /GRAVEL	2.5Y 3/4	10YR 5/8 @ 84"	LOOSE							

PARENT MATERIAL	GLACIAL TILL		PERCOLATION T			TESTS	I CERTIFY THAT ON 6/94 I HAV
DEPTH TO BEDROCK	>96"		TEST #	DEPTH	DATE	PERC. RATE	APPROVED BY THE DEPARTME THE ANALYSIS WAS PERFORE
STANDING WATER IN HOLE	N/A		1	40"	4-2-2024	2 MPI	TRAINING, EXPERTISE, AN
WEEPING FROM PIT FACE	84"		DEDC TO	CT DV	HILLAND VC	TDIID A	0
E.S.H.G.W. DEPTH	84" BELOW				JULIAN P. VOTRUBA CEDRIC RICHARDSON		SIGNATURE /u

RMED BY ME CONSISTANT WITH THE REQUIRED ND EXPERIENCE DESCRIBED IN 310 CMR 15.017



LOCUS

DESIGN DATA

TYPE OF BUILDING: SFH NO. OF BEDROOMS/EMPLOYEES: 3 NO GARBAGE GRINDER (DISPOSAL) ALLOWED DESIGN PERCOLATION RATE: 2 MPI LTAR: .74 DAILY FLOW: 3x110=330

> REQUIRED LEACHING AREA DESIGN FLOW / LTAR: 330/0.74=445.9 S.F. TOTAL LEACHING AREA = $(L \times W)$ $15 \times 30 = 450 \text{ S.F.}$

TOTAL DESIGN FLOW = LEACHING AREA x LTAR $450 \times 0.74 = 333 \text{ G.P.D.}$ DESIGN FLOW > DAILY FLOW 333 > 330

PRESBY PIPE REQUIRED (TABLE A IN MANUAL) = 210' 210' / 7 ROWS = 30' MIN. PER ROW (30' PROVIDED)MIN. SAND BED AREA = 432 sf. (PER MANUAL)

ASSESSOR'S REFERENCE |54-001-00053 W.D.R.D. REFERENCE BOOK 64617 PAGE 259 PLAN REFERENCE BOOK 20 PAGE 72 OWNER OF RECORD ATITUDE, LONGITUDE | 42.29071, -71.86075 ZONING REQUIREMENTS 40 FEET RESIDENTIAL FRONT SETBACK ZONING DISTRICT 65,340 S.F. MIN. LOT AREA SIDE SETBACK 20 FEET

THE WORK SHOWN DOES NOT ALTER A FLOOD PLAIN AS SHOWN ON THE FLOOD INSURANCE RATE MAP (F.I.R.M.) COMMUNITY PANEL NUMBER 25027C0611E DATED JULY 4, 2011.

REAR SETBACK

40 FEET

REPAIR SUBSURFACE SEWAGE DISPOSAL SYSTEM

CONTRACTOR TO VERIFY ACTUAL LOCATION OF EXISTING UTILITY SERVICES IN THE FIELD PRIOR TO CONSTRUCTION.

TYPICAL LEGEND										
IRON PIPE	0	EXIST. CONT. MAJ.	1000	WELL LOCATION	(W)					
CONCRETE BOUND		EXIST. CONT. MIN.	<u> </u>	PERC. TEST						
BOUNDARY LINE		PROP. CONT.	1100	DEEP HOLE						
ABUTTER LINE		WETLAND LINE	. — . —							
EASEMENT LINE		WETLAND BUFFER		BENCHMARK						
SETBACK LINE		EROSION CONTROL		DRAINAGE LINE						
STONEWALL	0000000000	PAVEMENT EXIST.		DRAIN MANHOLE	0					
TOEELINE		DAVEMENT DOOD		CATCLLBACIN						

PAUL M. LUKASON and JENNIFER L. SKORINKO, TRUSTEES OF THE LUKASON FAMILY 2019 IRREVOCABLE TRUST 5 DAWSON ROAD WORCESTER, MA. 01602

PROPERTY ADDRESS: 5 DAWSON ROAD WORCESTER, MA. 01602

150 FEET



MIN. FRONTAGE

New **E**ngland Environmental

P.O. Box 376 Rutland, MA 01543 Ph: (508) 829-7222 needllc@hotmail.com

SCALE: 1"=20' | SHEET: 1 OF 1 | JOB#: 19137-23



5/8/2024 5/28/2024 REVISED PER 5/20/24 EMAIL CONCERNING WETLANDS ACROSS STREET